



Technical Data Sheet

FINAL-KLEEN WAX & GREASE REMOVER

DESCRIPTION:

Final-Kleen is excellent for cleaning and degreasing bare metal, primed surfaces, and existing finishes prior to topcoating. Final-Kleen flashes quickly, leaving no residue.

PRODUCT & ADDITIVES:

PRODUCT	ITEM #	SIZE
Final-Kleen Wax & Grease Remover	9001	Gal
Final-Kleen Wax & Grease Remover	9005/9055	5 Gal/55 Drum

COMPATIBLE SUBSTRATES:

Final-Kleen may be used to clean:



- OEM Finishes &
- Cured Enamel & Lacquer Finishes
- Bare Metal
- Primed Surfaces

SAFETY ASPECTS:

Users should review the Safety Data Sheet (SDS) and product label for the material to be used to determine possible health hazards, appropriate engineering controls and precautions to be observed in the use of the material. Copies of the SDS and product label are available upon request.

INSRUCTIONS:



1. Wash surface with a mild detergent and water. Rinse and dry surface.
2. If necessary, sand or grind area to be repaired and blow away any sanding residue with compressed air.
3. Saturate a clean cloth with Final-Kleen
4. Wipe surface to be repaired thoroughly with Final-Kleen. Apply only to one panel at a time.
5. Remove immediately with a clean dry cloth.

Note: Do not allow Final-Kleen to dry on surface. If drying occurs, repeat application.

Note: Not recommended for temperatures below 60°F. Use in these temperatures will affect performance and dry times.

Note: Do Not use Final-Kleen Wax & Grease Remover on plastic parts because static electricity build up may cause flash fire. Use Autokote Plasti-Kleen anti-static surface cleaner instead.

Note: When cleaning and degreasing is completed, the surface must never be touched with the bare hand; as salts, moisture, and oils can be transferred to the prepared surface which may result in adhesion or blistering problems.



Technical Data Sheet

FINAL-KLEEN WAX & GREASE REMOVER

TECHNICAL DATA



Color	Clear
Coating V.O.C.	6.21 lbs/gal (744.1 g/l)
Package Size	Gallon, 5 Gallon, 55 Gal. Drum
Case Quantity	4 Gallons, 1-5 Gallon, 1-55 Gal Drum
Shelf Life	12 months unopened

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as Autokote Systems, LLC deems appropriate.