



ADVANCED REFINISH COMPONENTS

Technical Data Sheet

URETHANE REDUCER - MEDIUM

DESCRIPTION:

ARC Urethane Reducer - Medium is formulated for use in all urethane primers, clearcoats, and topcoats where a high quality reducer is required. This water-free, alcohol-free reducer produces excellent gloss and leveling. ARC Urethane Reducer - Medium is made from highest quality virgin solvents.

PRODUCT & ADDITIVES:

PRODUCT	ITEM #	SIZE
ARC Urethane Reducer - Medium	31870	Gallon
ARC Urethane Reducer - Medium	35870	5 Gallon

TEMPERATURE RANGE:

65° – 80°F (16° – 26°C)

SAFETY ASPECTS:

Users should review the Safety Data Sheet (SDS) and product label for the material to be used to determine possible health hazards, appropriate engineering controls and precautions to be observed in the use of the material. Copies of the SDS and product label are available upon request.

SUITABLE APPLICATIONS:

1. 2K Sealers
2. 2K Primers
3. Urethane Topcoats
4. Single Stage Urethane Topcoats

INSTRUCTIONS:

1. Refer to manufacturer's directions for proper mixing ratios.
2. Mix at proper ratio and stir thoroughly.
3. Reseal product after each use to prevent contamination.

CLEANING EQUIPMENT:

Clean equipment immediately with ARC lacquer thinner.

TECHNICAL DATA:


V.O.C. Limit	6.98 lbs/gal (837 g/l)
Package	31870 Gallon
Number per Case	4
Shelf Life	12 months unopened

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as Autokote Systems, LLC deems appropriate.

TDS #: ARC.31870/35870-E