

Technical Data Sheet

FISH EYE ELIMINATOR

DESCRIPTION:

Fish Eye Eliminator prevents fisheyes, craters and other surface defects in Single Stage polyurethane paints and two component urethane clears. Eliminator improves leveling, flow and gloss.

*SHAKE WELL PRIOR TO USING

PRODUCT & ADDITIVES:

PRODUCT	ITEM #	SIZE
Fish Eye Eliminator	162110	½ Pint

SAFETY ASPECTS:



Users should review the Safety Data Sheet (SDS) and product label for the material to be used to determine possible health hazards, appropriate engineering controls and precautions to be observed in the use of the material. Copies of the SDS and product label are available upon request.

DIRECTIONS:

Add Fish Eye Eliminator at the rate of ¼ ounce (1 capful) per sprayable pint.

COMPATIBLE SUBSTRATES:

Safe for most automotive finishes when used as directed.

TECHNICAL DATA:



Color	Clear
Mix Ratio	N/A
Regulatory V.O.C.	0.00 lb/gal 0.0 g/l
Actual V.O.C.	0.00 lb/gal 0.0 g/l
Package Size	Half Pint
Shelf Life	12 months unopened

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as Autokote Systems, LLC deems appropriate.